



proportional pressure regulator

VPPE-3-1/8-6-010

Part number: 539639

FESTO

Pressure regulation with electrical setpoint specification, suitable for block mounting



Data sheet

Feature	values
Nominal diameter, pressurisation	5 mm
Nominal diameter, exhaust	2.5 mm
Type of actuation	electrical
Sealing principle	soft
Assembly position	Any Preferably vertical
Design structure	Piloted piston regulator
Short circuit strength	for all electrical connections
Safety instructions	VPPE safety position: If the power supply cable is interrupted, output pressure is maintained unregulated.
Polarity protected	for all electrical connections
Valve function	3-way closed proportional-pressure regulator
Pressure regulation range	0.15 ... 6 bar
Inlet pressure 1	7 ... 8 bar
Max. pressure hysteresis	0.15 bar
Standard nominal flow rate	850 l/min
Switching time off	1,300 ms
Switching time on	550 ms
Operating voltage range DC	21.6 ... 26.4 V
Max. current consumption	150 mA
Max. electrical power consumption	3.6 W
Residual ripple	10 %
SETPOINT/ACTUAL values	Voltage type 0 - 10 V
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases
Note on operating and pilot medium	Lubricated operation not possible
CE mark (see declaration of conformity)	to EU directive for EMC
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Medium temperature	10 ... 50 °C
Protection class	IP65
Ambient temperature	10 ... 50 °C
Authorisation	RCM Mark c UL us - Listed (OL)
Product weight	445 g
Electrical connection	Plug Round design M12x1 4-pin
Mounting type	with through hole
Pneumatic connection, port 1	G1/8
Pneumatic connection, port 2	G1/8
Materials note	Conforms to RoHS
Materials information, housing	Wrought Aluminium alloy
Materials information for membrane	NBR