



solenoid valve

VZWP-L-M22C-N14-130-3AP4-40

Part number: 1489990

FESTO



Data sheet

Feature	values
Design structure	Pilot-actuated piston poppet valve
Type of actuation	electrical
Sealing principle	soft
Assembly position	Coil preferably on top
Mounting type	Line installation
Process valve connection	NPT 1/4
Electrical connection	Plug Cubic design to EN 175301-803 Design A
Nominal size	13 mm
Valve function	2/2 closed, monostable
Manual override	None
Flow direction	non reversible
Medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases Neutral fluids Other media on request
Nominal pressure of process valve	40
Differential pressure	0.5 bar
Characteristic coil data	230 V AC: 50/60 Hz, pick-up power 10.5 VA, holding power 7.6 VA
Insulation class	H
Permissible voltage fluctuation	+/- 10 %
Duty cycle	100%
Type of piloting	Piloted
Medium pressure	0.5 ... 40 bar
Max. viscosity	22 mm ² /s
Medium temperature	-10 ... 80 °C
Ambient temperature	-10 ... 35 °C
Leak rate in accordance with EN 12266-1	A
Flow rate Kv	1.5 m ³ /h
Standard nominal flow rate	1,600 l/min
Switching time on	100 ms
Switching time off	250 ms
Materials note	Contains PWIS substances Conforms to RoHS
Materials information, housing	Cast brass
Material number for housing	CW617N
Materials information for seals	NBR
Screw material data	High alloy steel, non-corrosive
Material number, screw	1.4301
Product weight	600 g
Protection class	IP65
CE mark (see declaration of conformity)	to EU directive low-voltage devices
Corrosion resistance classification CRC	1 - Low corrosion stress