



proportional pressure regulator VPPM-6F-L-1-F-0L2H-LK-S1

Part number: 8031107

FESTO



Data sheet

| Feature | values |
|---|--|
| Nominal diameter, pressurisation | 6 mm |
| Nominal diameter, exhaust | 4.5 mm |
| Type of actuation | electrical |
| Sealing principle | soft |
| Assembly position | Any |
| Design structure | Pilot actuated diaphragm regulator |
| Short circuit strength | for all electrical connections |
| Safety instructions | VPPM safety position: If the power supply cable is interrupted, output pressure is maintained unregulated. |
| Polarity protected | for all electrical connections |
| Type of reset | mechanical spring |
| Type of piloting | Piloted |
| Valve function | 3-way proportional-pressure regulator |
| Type of display | LED |
| Pressure regulation range | 0.02 ... 2 bar |
| Inlet pressure 1 | 0 ... 4 bar |
| Max. pressure hysteresis | 0.01 bar |
| Standard nominal flow rate | 380 l/min |
| Operating voltage range DC | 18 ... 30 V |
| Max. current consumption | 300 mA |
| Duty cycle | 100% |
| Max. electrical power consumption | 7 W |
| Protocol | I-Port IO-Link |
| Residual ripple | 10 % |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases |
| Note on operating and pilot medium | Lubricated operation not possible |
| CE mark (see declaration of conformity) | to EU directive for EMC |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Medium temperature | 10 ... 50 °C |
| Protection class | IP65 |
| Ambient temperature | 0 ... 60 °C |
| Authorisation | RCM Mark c UL us - Listed (OL) |
| Product weight | 400 g |
| Linearity error, FS | 1 % |
| Temperature coefficient | 0.04 %/K |
| FS repetition accuracy | 0.5 % |
| IO-Link, protocol | Device V 1.1 |
| IO-Link, communication mode | COM1. COM2. COM3. |
| IO-Link, port type | A |
| IO-Link, process data width OUT | 2 Byte |
| IO-Link, process data width IN | 2 Byte |
| IO-Link, minimum cycle time | 0,5 ms |
| Mounting type | Optional |

| Feature | values |
|--------------------------------|---------------------------------------|
| | with through hole with accessories |
| Pneumatic connection, port 1 | Sub-base |
| Pneumatic connection, port 2 | Sub-base |
| Pneumatic connection, port 3 | Sub-base |
| Materials note | Conforms to RoHS |
| Materials information, housing | Wrought Aluminium alloy Anodised |