



one-way flow control valve GRLA-1/2-QS-12-RS-D

Part number: 534344

★ Core product range

With knurled screw and lock nut

FESTO



Data sheet

Feature	values
Valve function	One-way flow control function
Pneumatic connection, port 1	QS-12
Pneumatic connection, port 2	G1/2
Adjusting element	Knurled screw
Mounting type	Threaded with external (male) thread
Standard nominal flow rate in flow control direction	1,580 l/min
Standard nominal flow rate in non-return direction	925 ... 1605 l/min
Operating pressure	0.2 ... 10 bar
Ambient temperature	-10 ... 60 °C
Authorisation	Germanischer Lloyd
Assembly position	Any
Operating pressure complete temperature range	0.2 ... 10 bar
Standard flow rate in direction of flow control: 6 -> 0 bar	2,220 l/min
Standard flow rate in blocked direction: 6 -> 0 bar	1910 ... 2500 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Storage temperature	-10 ... 40 °C
Medium temperature	-10 ... 60 °C
Nominal tightening torque	15 Nm
Product weight	124 g
Materials note	Conforms to RoHS
Materials information for seals	NBR
Material information, hollow bolt	Wrought Aluminium alloy Anodised
Release ring material data	POM
Material information, knurled head	Wrought Aluminium alloy Anodised
Regulating screw material data	High alloy steel, non-corrosive
Swivel joint material data	Zinc die-casting