



# solenoid valve MFH-5/3E-D-3-C

Part number: 151874

FESTO

With manual override, without solenoid coil or socket. Solenoid coil and socket should be ordered separately.



## Data sheet

| Feature                               | values   |
|---------------------------------------|--|
| Valve function                        | 5/3 exhausted  |
| Type of actuation                     | electrical   |
| Width                                 | 65 mm  |
| Standard nominal flow rate            | 4,600 l/min  |
| Operating pressure                    | 3 ... 10 bar   |
| Design structure                      | Piston slide   |
| Type of reset                         | mechanical spring  |
| Protection class                      | IP65   |
| Authorisation                         | Germanischer Lloyd   |
| Nominal size                          | 14.5 mm  |
| Grid dimension                        | 71 mm  |
| Exhaust-air function                  | throttleable   |
| Sealing principle                     | soft   |
| Assembly position                     | Any  |
| Conforms to standard                  | ISO 5599-1   |
| Manual override                       | with accessories, detenting<br>Pushing   |
| ISO code                              | 357  |
| Type of piloting                      | Piloted  |
| Pilot air supply                      | Internal   |
| Flow direction                        | non reversible   |
| Freedom from overlap                  | Yes  |
| Note on forced dynamisation           | Switching frequency at least once a week   |
| Switching time off                    | 78 ms  |
| Switching time on                     | 37 ms  |
| Max. positive test pulse with logic 0 | 2,200 µs   |
| Max. negative test pulse with logic 1 | 3,700 µs   |
| Operating medium                      | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Note on operating and pilot medium    | Lubricated operation possible (subsequently required for further operation)                    |
| Vibration resistance                  | Transport application test at severity level 1 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance                      | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27              |
| Medium temperature                    | -10 ... 60 °C  |
| Sound pressure level                  | 85 dB(A)   |
| Ambient temperature                   | -5 ... 40 °C   |
| Product weight                        | 1,040 g  |
| Electrical connection                 | Via F coil, must be ordered separately   |
| Mounting type                         | On sub-base<br>With through-hole and screw   |
| Pilot exhaust port 82                 | M5   |
| Pilot exhaust port 84                 | M5   |

| Feature                         | values                                    |
|---------------------------------|---|
| Pneumatic connection, port 1    | Connection plate size 3 as per ISO 5599-1 |
| Pneumatic connection, port 2    | Connection plate size 3 as per ISO 5599-1 |
| Pneumatic connection, port 3    | Connection plate size 3 as per ISO 5599-1 |
| Pneumatic connection, port 4    | Connection plate size 3 as per ISO 5599-1 |
| Pneumatic connection, port 5    | Connection plate size 3 as per ISO 5599-1 |
| Materials note                  | Conforms to RoHS                          |
| Materials information for seals | HNBR<br>NBR                               |
| Materials information, housing  | Aluminium die cast                        |