


# semi-rotary drive DRRD-12-

Part number: 574398

FESTO



Exemplary  
representation

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	values
Size	12
Swivel angle	180 deg
Cushioning	P: Flexible cushioning rings/plates at both ends Y9: internal hydraulic cushioning normal Y12: external hydraulic cushioning
Assembly position	Any
Design structure	Rack and pinion
Max. number of intermediate positions	1
Position detection	For proximity sensor
Operating pressure	2 ... 10 bar
Mode of operation	double-acting
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Ambient temperature	-10 ... 60 °C
Theoretical torque at 6 bar	0.8 Nm
Permissible mass moment of inertia	0.008 ... 0.03 kgm <sup>2</sup>
Mounting type	Optional with through hole with internal (female) thread
Pneumatic connection	M5
Materials note	Contains PWIS substances Conforms to RoHS
Materials information for drive shaft	High alloy steel, non-corrosive
Materials information for seals	NBR TPE-U(PU)
Materials information, housing	Wrought Aluminium alloy Smooth anodised