























163496 DNC-125- -PPV-A (Standard cylinder) — Series: All

| 163496 DNC-125- -PPV-A (Standard cylinder) | | | | | | |
|--|----------|--|------|------|---|---|
| Pos. | Part no. | Type Article designation | Qty. | Unit | Hint | Order |
| 999 | 369201 | DNC-125- PPVA Set of wearing parts | 1 | PC | Spare parts: 2, 5, 10, 13, 14, 16, 22, 23. |  |
| 1 | 223527 | DIN 439-B-M27X2-04 Hex nut | 1 | PC | |  |
| 2 | 673133 | WIFC2-32X42X11,2-TPE-U Wiper seal | 1 | PC | Grease during re-assembly. See position no. 22 |  |
| 3 | | SINT-B50 32X40X40 Cylinder bearing | 1 | PC | Not available separately, see position 7 |  |
| 4 | | DNC-125 Bearing cap | 1 | PC | Not available separately, see position 7 |  |
| 5 | | 40 FPM Buffer seal | 2 | PC | Not available separately, see position 7 / 21 / 999 Grease during re-assembly. See position no. 22 |  |
| 6 | | DSBX-125 Ring | 1 | PC | Not available separately, see position 7 |  |
| 7 | 124060 | DNC-125-PPV Bearing cap module | 1 | PC | |  |
| 8 | 693437 | M8X55-10.9 Flue screw | 8 | PC | Use thread locking agent. See position no. 23 Tightening torque 40 Nm / 29.5 lbf ft |  |
| 9 | 237072 | DIN 125-A-8,4-A2 Disc | 8 | PC | |  |
| 10 | | DNC-125 PU Cushioning disc | 2 | PC | Not available separately, see position 999 |  |
| 11 | 187788 | DNC-125- -ET Piston rod | 1 | PC | When ordering please specify the configuration (see type plate) |  |
| 12 | 223084 | 125-PPV Buffer sleeve | 2 | PC | |  |
| 13 | | 125X110X10 Lip ring | 2 | PC | Not available separately, see position 999 Grease during re-assembly. See position no. 22 |  |
| 14 | | DN -125 Guiding band | 1 | PC | Not available separately, see position 999 |  |
| 15 | 216909 | 7X7X353,5 Magnetic tape | 1 | PC | |  |
| 16 | | B-20X2-N-NBR70 O-ring ISO3601 | 1 | PC | Not available separately, see position 999 Grease during re-assembly. See position no. 22 |  |
| 17 | | DNC-125 Piston | 1 | PC | Not available | |
| 18 | 364164 | DNC-125 Threaded coupling | 1 | PC | Use thread locking agent. See position no. 23 Tightening torque 170 Nm / 125.4 lbf ft |  |
| 19 | | DNC-125- Cylinder barrel | 1 | PC | Not available Grease during re-assembly. See position no. 22 | |
| 20 | | DNC-125 End cap | 1 | PC | Not available separately, see position 21 |  |
| 21 | 124061 | DNC-125- PPV-A End cap | 1 | PC | |  |
| 22 | 684474 | LUB-KC1 SILIKONFREI 20ML Lubricating grease | 1 | PC | |  |
| 23 | 384267 | LOCTITE-243-10ML Adhesive bonding agent | 1 | PC | |  |