


# Push-in Y-connector QSY-12-20

Part number: 130811

FESTO



## Data sheet

| Feature                                  | values   |
|--|--|
| Size                                     | Standard   |
| Nominal size                             | 7 mm   |
| Assembly position                        | Any  |
| Container size                           | 20   |
| Design structure                         | Push/pull principle                                      |
| Temperature dependent operating pressure | -0.95 ... 14 bar   |
| Operating medium                         | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Note on operating and pilot medium       | Lubricated operation possible                            |
| Corrosion resistance classification CRC  | 1  |
| Ambient temperature                      | -10 ... 80 °C  |
| Authorisation                            | Germanischer Lloyd                                       |
| Product weight                           | 37 g   |
| Number of outputs                        | 2  |
| Number of supply lines                   | 1  |
| Pneumatic connection, supply line        | for tubing, 12mm outside diameter                        |
| Pneumatic connection, output             | for tubing, 12mm outside diameter                        |
| Colour of release ring                   | blue   |
| Materials note                           | Conforms to RoHS   |
| Materials information, housing           | PBT  |
| Release ring material data               | POM  |
| Materials information for tubing seal    | NBR  |
| Hose clamping segment material data      | High alloy steel, non-corrosive                          |