



lubricator MS4-LOE-1/8-R

Part number: 529413

FESTO

Plastic bowl with plastic bowl guard, direction of flow: from left to right.



Data sheet

| Feature | values |
|---|---|
| Size | 4 |
| Series | MS |
| Assembly position | Vertical +/- 5° |
| Design structure | proportional standard mist lubricator |
| Max. oil capacity | 30 cm ³ |
| Bowl guard | Plastic guard |
| Operating pressure | 1 ... 12 bar |
| Minimum flow rate for lubricator function | 40 l/min |
| Standard nominal flow rate | 1,100 l/min |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases |
| Note on operating and pilot medium | Lubricated operation possible |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Storage temperature | -10 ... 60 °C |
| Medium temperature | -10 ... 60 °C |
| Oil viscosity | ISO VG 32 |
| Ambient temperature | -10 ... 60 °C |
| Product weight | 194 g |
| Mounting type | Optional Line installation with accessories |
| Pneumatic connection, port 1 | G1/8 |
| Pneumatic connection, port 2 | G1/8 |
| Materials note | Conforms to RoHS |
| Materials information, housing | Aluminium die cast |
| Materials information for bowl | PC |