

## short-stroke cylinder ADVC-80-15-A-P-A Part number: 188317

**FESTO** 

For proximity sensing, piston-rod end with male thread.





## **Data sheet**

Feature	values
Stroke	15 mm
Piston diameter	80 mm
Based on the standard	ISO 6431
	Hole pattern
	VDMA 24562
Cushioning	P: Flexible cushioning rings/plates at both ends
Assembly position	Any
Mode of operation	double-acting
Design structure	Piston
	Piston rod
Position detection	For proximity sensor
Operating pressure	1 10 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Corrosion resistance classification CRC	1 - Low corrosion stress
Ambient temperature	-20 80 °C
Theoretical force at 6 bar, return stroke	2,827 N
Theoretical force at 6 bar, advance stroke	3,016 N
Moving mass	289 g
Product weight	1,940 g
Mounting type	Optional
	with through hole
	with accessories
Pneumatic connection	G1/8
Materials note	Free of copper and PTFE
Materials information for cover	Wrought Aluminium alloy
	Anodised
Materials information for seals	TPE-U(PU)
Materials information, housing	Wrought Aluminium alloy
	Anodised
Materials information for piston rod	High alloy steel