


# activated carbon filter LFX-1/2-D-MAXI

Part number: 532785

FESTO

High performance filter for virtually oil-free, odourless compressed air, suitable for use in the food processing industry



## Data sheet

Feature	values
Size	Maxi
Series	D
Assembly position	Vertical +/- 5°
Design structure	Active carbon filter Fibre filter
Bowl guard	Metal bowl guard
Operating pressure	0 ... 16 bar
Recommended maximum standard flow rate	1,100 l/min
Max. standard flow rate for air quality class	1,100 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [1:4:2] Inert gases
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Storage temperature	-10 ... 60 °C
Air purity class at output	Compressed air to ISO 8573-1:2010 [1:4:1] Inert gases
Medium temperature	5 ... 30 °C
Residual oil content	<= 0.003 mg/m3
Ambient temperature	-10 ... 60 °C
Product weight	1,191 g
Mounting type	Optional Line installation With mounting bracket
Pneumatic connection	G1/2
Pneumatic connection, port 1	Sub-base G1/2
Pneumatic connection, port 2	Sub-base G1/2
Materials note	Free of copper and PTFE Conforms to RoHS
Materials information for filter	Active carbon Mesh
Materials information, housing	Zinc die-casting
Materials information for bowl	PC