


# push-in fitting NPQM-D-G18-Q4-P10

Part number: 558661

FESTO



## Data sheet

| Feature                                       | values  |
|---|---|
| Size  | Standard  |
| Nominal size                                  | 3 mm  |
| Type of seal on screw-in stud                 | Sealing ring  |
| Design structure                              | Push/pull principle   |
| Operating pressure complete temperature range | -0.95 ... 16 bar  |
| Operating medium                              | Compressed air in accordance with ISO8573-1:2010 [7:-:-]<br>Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a> |
| Note on operating and pilot medium            | Lubricated operation possible   |
| Corrosion resistance classification CRC       | 1 - Low corrosion stress  |
| Ambient temperature                           | -20 ... 70 °C   |
| Nominal tightening torque                     | 6 Nm  |
| Tolerance for nominal tightening torque       | ± 20 %  |
| Product weight                                | 6.1 g   |
| Pneumatic connection, port 1                  | G1/8  |
| Pneumatic connection, port 2                  | For tubing outside diameter 4 mm  |
| Materials note                                | Conforms to RoHS  |
| Materials information, housing                | Nickel-plated brass   |
| Materials information for tubing seal         | NBR   |