

push-in fitting CRQS-1/4-10-I

Part number: 132333

FESTO

male thread with internal hexagon socket.



Data sheet

| Feature | values |
|---|---|
| Size | Standard |
| Nominal size | 5.9 mm |
| Assembly position | Any |
| Container size | 1 |
| Design structure | Push/pull principle |
| Operating pressure complete temperature range | -0.95 ... 10 bar |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:-:-] Water as per manufacturer's declaration at www.festo.com |
| Note on operating and pilot medium | Lubricated operation possible |
| Corrosion resistance classification CRC | 4 - Very high corrosion stress |
| Food-safe | See Supplementary material information |
| Ambient temperature | -15 ... 120 °C |
| Authorisation | Germanischer Lloyd |
| Product weight | 21 g |
| Usable wires | PFAN |
| Pneumatic connection, port 1 | Male thread R1/4 |
| Pneumatic connection, port 2 | For tubing outside diameter 10 mm |
| Materials note | Conforms to RoHS |
| Materials information, housing | High alloy steel, non-corrosive |
| Release ring material data | High alloy steel, non-corrosive |
| Materials information for tubing seal | FPM |
| Hose clamping segment material data | High alloy steel, non-corrosive |