

fine filter combination LFMBA-1/4-D-MIDI Part number: 186471

FESTO

Micro filter 1 μm for prefiltration and micro filter 0.01 $\mu m,$ with metal bowl guard.





Data sheet

| Feature | values |
|----------------------------------|--|
| Size | Midi |
| Series | D |
| Assembly position | Vertical +/- 5° |
| Grade of filtration | 0.01 µm |
| Filter efficiency | 99.9999 % |
| Condensate drain | manual rotary |
| Design structure | Fibre filter |
| Max. condensate volume | 43 ml |
| Bowl guard | Metal bowl guard |
| Operating pressure | 1 16 bar |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [6:8:4] |
| | Inert gases |
| Air purity class at output | Compressed air in accordance with ISO8573-1:2010 [1:7:2] |
| | Inert gases |
| Medium temperature | 1.5 60 °C |
| Residual oil content | 0.01 mg/m3 |
| Ambient temperature | -10 60 °C |
| Product weight | 1,300 g |
| Mounting type | Line installation |
| | with accessories |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 2 | G1/4 |
| Materials note | Free of copper and PTFE |
| | Conforms to RoHS |
| Materials information for filter | Boron silicate fibre |
| Materials information, housing | Zinc die-casting |
| Materials information for bowl | PC |