

proportional pressure regulator VPPM-6L-L-1-G18-0L10H-A4P-S1C1

Part number: 558336

FESTO



Data sheet

| Feature | Value |
|---|--|
| Nominal diameter, pressurisation | 6 mm |
| Nominal diameter, exhaust | 4.5 mm |
| Type of actuation | electrical |
| Sealing principle | soft |
| Assembly position | Any |
| Design structure | Pilot actuated diaphragm regulator |
| Short circuit strength | for all electrical connections |
| Safety instructions | VPPM safety position: If the power supply cable is interrupted, output pressure is maintained unregulated. |
| Polarity protected | for all electrical connections |
| Type of reset | mechanical spring |
| Type of piloting | Piloted |
| Valve function | 3-way proportional-pressure regulator |
| Type of display | Backlit LCD |
| Pressure regulation range | 0.1 ... 10 bar |
| Inlet pressure 1 | 0 ... 11 bar |
| Max. pressure hysteresis | 0.05 bar |
| Standard nominal flow rate | 1,400 l/min |
| Operating voltage range DC | 21.6 ... 26.4 V |
| Max. current consumption | 300 mA |
| Duty cycle | 100 % |
| Max. electrical power consumption | 7 W |
| Residual ripple | 10 % |
| Switch output | PNP |
| Signal range, analogue output | 4 - 20 mA |
| Signal range, analogue input | 4 - 20 mA |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases |
| Note on operating and pilot medium | Lubricated operation not possible |
| Authorisation | RCM Mark c UL us - Listed (OL) |
| KC mark | KC-EMV |
| CE mark (see declaration of conformity) | to EU directive for EMC |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Medium temperature | 10 ... 50 °C |
| Protection class | IP65 |
| Ambient temperature | 0 ... 50 °C |
| Product weight | 400 g |
| Linearity error, FS | 1 % |
| Temperature coefficient | 0.04 %/K |
| FS repetition accuracy | 0.5 % |
| Electrical connection | 8-pin M12 Plug |
| Mounting type | with through hole with accessories |

| Feature | Value |
|------------------------------|-------------------------------------|
| | Optional |
| Pneumatic connection, port 1 | G1/8 |
| Pneumatic connection, port 2 | G1/8 |
| Pneumatic connection, port 3 | G1/8 |
| Materials note | Conforms to RoHS |
| Material housing | Wrought Aluminium alloy Anodised |